

Product data			
Sort: OPPTape		Model: B655	
Tape composition	Releasing	Backing:OPP	Acrylic water base
Characteristic:			
Item	Unit	Standard	Test standard
Total Thickness	μ m	55±2	GB/7125-1999
180° Peel strength (to steel)	N/IN	≥4.5	GB/2792-1998
Tensile Strength	N/IN	≥70-100	GB/7753-1987
Elongation	%	100	ASTM D-1000
Specification: General purpose			
Application: For carton sealing, Packaging			
Color: Yellow, Clear, Brown			
Transportation and Storage:			
<ul style="list-style-type: none"> ● Jumbo roll should be transported and placed vertically, and avoid squeeze adhesive ● Product should be stored in cool and dry area away from direct sunlight, air conditioner and other high temperature heat sources ● Product should be placed in temperature 20°C-30°C, Humidity: 40%-70% area, Should be used within 6 months from the date of production 			
Note: adherend should be clean, dry, no grease or other contamination			
Other: corresponds toRoHS			
Remarks: The characteristics are obtained from tests recommended by GB standard, in actual application, individual roll may vary slightly from different backing, method and environment, used massively as well as it is qualified			
Author: 陈足照		Auditor: 许金章	Approval: 刘忠建
Issuance: 2017-03-31		Version: QR-JS	